



Oracle Database Performance Tuning: The No SQL Option

Daniel A. Morgan

11 June, 2015

Daniel A. Morgan



🏆 Oracle ACE Director

- Educator



Wrote Oracle curriculum and primary program instructor at University of Washington



Oracle Consultant: Harvard University

- University Guest Lecturers
 - APAC: University of Canterbury (NZ)
 - EMEA: University of Oslo (Norway)
 - Latin America: Universidad Latina de Panama and Technologico de Costa Rica
- The Morgan behind Morgan's Library on the web
www.morganslibrary.org
- 10g, 11g, and 12c Beta tester
- Retired chair Washington Software Assoc. Database SIG
- Co-Founder International GoldenGate Oracle Users Group

The Morgan's Library Web Site



Morgan's Library

www library

International Oracle Events 2015-2016 Calendar

FebMarAprMayJunJulAugSepOctNovDecJan

The Library

The library is a spam-free on-line resource with code demos for DBAs and Developers. If you would like to see new Oracle database functionality added to the library ... just email us. Oracle 12.1.0.2.0 has been released and new features will be showing up for many weeks. The first updates have already been made.

Home

Resources

- [Library](#)
- [How Can I?](#)
- [Code Samples](#)
- [Presentations](#)
- [Links](#)
- [Book Reviews](#)
- [Downloads](#)
- [User Groups](#)
- [Blog](#)
- [Humor](#)

General

- [Contact](#)
- [About](#)
- [Services](#)
- [Legal Notice & Terms of Use](#)
- [Privacy Statement](#)

Presentations Map



MadDog Morgan



Training Events and Travels

- [IOUG, Chicago, Illinois - Mar 10](#)
- [UTOUG, Salt Lake City, Utah - Mar 11-12](#)
- [OUGN, Oslo, Norway - Mar 12-14](#)
- [Collaborate, Las Vegas, Nevada - Apr 12-16](#)
- [NYOUG, New York, NY - May 19](#)
- [GLOC, Cleveland, Ohio - May 19-20](#)

Next Event: 27 January, Redwood Shores, CA

Oracle Events



Click on the map to find an event near you

Morgan



aboard USA-71



Library News

- [Morgan's Blog](#)
- [Join the Western Washington OUG](#)
- [Morgan's Oracle Podcast](#)
- [US Govt. Mil. STIGs \(Security Checklists\)](#)
- [Bryn Llewellyn's PL/SQL White Paper](#)
- [Bryn Llewellyn's Editioning White Paper](#)
- [Explain Plan White Paper](#)



ACE News

 Would you like to become an Oracle ACE? 

Learn more about becoming an ACE



- [ACE Directory](#)
- [ACE Google Map](#)
- [ACE Program](#)
- [Stanley's Blog](#)

Congratulations to our newest ACE Director Jim Czuprynski


Daniel A. Morgan | damorgan12c@gmail.com | www.morganslibrary.org

3

No SQL Performance Tuning

Presented: APAC Tokyo - June, 2015

IGGOUG: The New Users Group In The Neighborhood



The screenshot shows the homepage of the International GoldenGate Oracle Users Group (IGGOUG). The browser address bar shows 'www.iggoug.org'. The page has a red header with the group's name. The main content is organized into several columns and sections:


- Oracle GG Documentation:** A list of links including '12c GoldenGate', '11.2.1 GoldenGate', '11.1.1.1 GoldenGate', '11.1.1 GoldenGate', '10.4 GoldenGate', and 'Oracle Database'.
- Blogs & Links:** A section for blogs, links, sample code, and tricks related to GoldenGate.
- SOS: Support Our Sponsors:** A section thanking supporters and sponsors.
- Welcome Message:** A central text block welcoming visitors and explaining the group's purpose. It includes a 'Click Here' link and a table of supported database vendors.
- 2014 Organizational Meeting:** A section announcing a meeting in San Francisco at OpenWorld 2014.
- Training Programs:** A section offering hands-on classes for Oracle, SQL Server, and DB2.
- Oracle ACE Programs:** A section for finding Oracle ACEs and becoming one.
- Leadership Team:** A section introducing the leadership team.

At the bottom, there are red buttons for 'Contact', 'Members', and 'Terms of Use'.

Oracle	Sybase ASE
DB2	Teradata
SQL Server	... and more

www.iggoug.org

cd \$ORACLE_BASE




Travel Log: OTN LAD Tour 2014



Travel Log: Tokyo 2006 / www.aozora.co.jp

The screenshot shows the Aozora Bank website interface. At the top, there's a navigation bar with links like '個人のお客さま' (Individual Customers), '法人のお客さま' (Corporate Customers), '株主・投資家の皆さま' (Shareholders/Investors), 'あおぞら銀行について' (About Aozora Bank), and '採用情報' (Recruitment Information). Below this, a red-bordered box contains two important notices in Japanese regarding internet banking security and software updates. The main content area features a large advertisement for 'MuniFin' (Municipal Finance) with details about a 5-year loan program, including interest rates and terms. To the right, there's a section for 'インターネットバンキング' (Internet Banking) with login and application links. At the bottom, there's a section for 'お得なキャンペーン・プラン' (Beneficial Campaigns/Plans) featuring various financial products like '円定期預金' (Japanese Yen Fixed Deposit), '投資信託' (Investment Trust), and 'キャッシュカード・プラス' (Cash Card Plus).

Travel Log: Tokyo 2006 / www.aozora.co.jp/english



The #1 Database Performance Tuning Mythology

Instance Efficiency Percentages (Target 100%)

Buffer Nowait %:	99.80	Redo NoWait %:	100.00
Buffer Hit %:	97.34	In-memory Sort %:	99.99
Library Hit %:	99.97	Soft Parse %:	98.79
Execute to Parse %:	99.29	Latch Hit %:	99.57
Parse CPU to Parse Elapsed %:	0.00	% Non-Parse CPU:	96.60

This is from the worst performing Oracle Database I've seen since 2006

The #1 Database Performance Tuning Methodology

Guessing



One Solution

BAAG Party - Battle Against Any Guess

Home of the BAAG Party

[Blog](#) [About BAAG](#) [BAAG Comrades](#) [Join BAAG](#)

search blog archives

#BAAG on Twitter

Recent Posts

- [The Statspack for PostgreSQL — Meet Pgstatspack](#)
- [SQL Server Performance Diagnostic — Still Guessing?](#)
- [Welcome ASH Masters!](#)
- [BAAG Members page change](#)
- [Avoiding Guesswork in Complex Environments](#)

Recent Comments

- [Alex Gorbachev on Avoiding Guesswork in Complex Environments](#)
- [Graham Oakes on Avoiding Guesswork in Complex](#)

About BAAG

Battle Against Any Guess

BAAG - what is it all about? The main idea is to eliminate guesswork from our decision making process — once and for all. It's not Oracle specific even though the roots lie in the area of Oracle database administration. So keep reading even if you don't know anything about Oracle or computers. Before we go any further I should say that the title was inspired by another fine BAA... site — [BAARF](#). Just to avoid any guesses. 😊

After some mental fermentation the [birth](#) of BAAG had been finally triggered by an Oracle-L [thread](#) started as [10gR2 performance sux](#). Title of the post was a direct consequence of pure guess and, worse yet, uneducated guess. It's also interesting to see how the thread [developed](#) - guesswork. [Another problem](#) in the same thread was followed up by the same troubleshooting style. Perhaps, the author, inspired by previous responses, also hoped to find the magic solution from of Oracle-L powered (and often educated) guesses.

Database performance tuning is one of the most noticeable areas where guesswork is still flourishing. There were quite a few methodological techniques born recently, such as [YAPP](#) and [Method R](#), and older guess-based methods such as [Tuning by BCHR](#) are going away. Nevertheless, people's mentality is very difficult to change and we keep relying on guesswork hoping to solve the issue faster. Hope-powered guess is the evil.

Performance tuning is just one example. Imagine that your Oracle database crashes with ORA-600 and guesswork starts powered by your experience. Depending how good your memory and experience are you might want to ask in an Oracle forum something like "My database x.x.x.x crashed with ORA-600. Anyone seen it?" It's fishing for a

MySQL

- [Baron Schwartz](#)
- [Peter Zaitsev](#)
- [Pythian Blog \(MySQL\)](#)

Oracle

- [Anjo Kolk](#)
- [ASH Masters](#)
- [Cary Millsap](#)
- [Daniel Fink](#)
- [James Morle](#)
- [Jonathan Lewis](#)
- [Mogens Nørgaard](#)
- [Niall Litchfield](#)
- [Pythian Blog \(Oracle\)](#)
- [Tanel Poder](#)
- [Tom Kyte](#)

PostgreSQL

- [Pgstatspack](#)

BAAG Comrades

7-Sep-08	Mohammad Illiyaz http://	BAAG Member	Because i also want to BATTLE AGAINST ANY GUESSES
22-Sep-08	Ken Jordan http://	BAAG Member	Seeking THE truth!
27-Sep-08	Martin Berger http://berx.at	BAAG Member	I travel on a sea of wild guesses, with some islands of educated guesses. Knowledge is the stars which help me traveling on these seas. I need more light!
22-Nov-08	Daniel Morgan http://www.morganslibrary.org	BAAG Member	Too often a conclusion is simply the place where someone became tired of thinking. Then the "answer" becomes a guess, a prejudice, or a retreat to mythology. I prefer the application of synapses.
11-Feb-09	Fairlie Rego http://www.el-caro.blogspot.com	BAAG Member	becoz I have had enuff
3-Mar-09	Olivier NOEL http://	BAAG Member	Help me in my daily struggle against Oracle
16-Mar-09	Michael Erwin http://www.oracle.com/consulting/technology/grid-computing.html	BAAG Member	I like sharing what I know as actual fact vs. guessing as well.
18-Mar-09	Randolf Geist http://oracle-randolf.blogspot.com/	BAAG Member	I guess (!) it's time to join.
1-Apr-09	Kevin Fries http://	BAAG Member	I guess it cannot make things worse, I've tried everything else and the Magic 8-Ball broke.
13-Apr-09	Henrik Harsfort http://	BAAG Member	to guess is to not know.
24-Apr-09	Paul Clare http://	BAAG Member	Creative problem solving is evolving into an art form.



BAAG Membership




Christian Antognini
 Karl Arao
 Mark Bobak
 Ronald Bradford
 Wolfgang Breitling
 Doug Burns
 Andrew Clarke
 Randolf Geist
 Alex Gorbachev
 Marco Gralike
 Frits Hoogland
 John Hurley
 Anjo Kolk
 David Kurtz
 Jonathan Lewis
 Robyn Sands
 Jared Still
 Jeremiah Wilton

Clearly

- No surprise ... I do not endorse guessing
 - Possibly a big surprise ... I do not like normal AWR reports
 - I think the solutions to every performance issue is an Exadata
 - And I am not attracted to all the tools with pretty GUIs
 - So let us take a deep dive into performance tuning and address the root cause of the majority of issues I see in my work
 - We will focus on what fixes all issues ... not just one issue
 - We all know that 30+ years of doing it the way we have been
 - DBMS_SUPPORT introduced with version 7.2
 - DBMS_TRACE introduced with version 8.1.5
 - DBMS_MONITOR introduced with version 10.1
- has not eliminated tuning problems

What Affects Performance

- Hardware
 - Servers
 - Storage Subsystems
 - Networks
- Software
 - Operating System Configuration
 - Virtual Machines
 - Drivers
- Database
 - Memory Allocation
 - Optimizer Configuration
 - SQL Quality
- Application
 - Web Servers
 - Application Servers
 - Middleware Caching
 - Application Code Quality



Hardware

- Servers and Operating Systems
 - Blade Servers
 - I/O Cards
 - NUMA Architecture
 - HugePages
 - Swapiness
- Virtual Machines
- Storage
 - Controllers
 - Read-Write Caches
 - LUN Size and Layout
- Networks
 - TCP/IP
 - UDP



Blade Servers (1:2)

- Suitable for web and application servers
- Possibly usable for small databases
- A meltdown waiting to happen with RAC



RAC: Frequently Asked Questions (Doc ID 220970.1)

Cluster interconnect network separation can be satisfied either by using standalone, dedicated switches, which provide the highest degree of network isolation, or Virtual Local Area Networks defined on the Ethernet switch, which provide broadcast domain isolation between IP networks. VLANs are fully supported for Oracle Clusterware interconnect deployments. Partitioning the Ethernet switch with VLANs allows for:

- Sharing the same switch for private and public communication.
- Sharing the same switch for the private communication of more than one cluster.
- Sharing the same switch for private communication and shared storage access.

The following best practices should be followed:

The Cluster Interconnect VLAN must be on a non-routed IP subnet.

All Cluster Interconnect networks must be configured with non-routed IPs. The server-server communication should be single hop through the switch via the interconnect VLAN. There is no VLAN-VLAN communication.

Oracle recommends maintaining a 1:1 mapping of subnet to VLAN.

The most common VLAN deployments maintain a 1:1 mapping of subnet to VLAN. It is strongly recommended to avoid multi-subnet mapping to a single VLAN. Best practice recommends a single access VLAN port configured on the switch for the cluster interconnect VLAN. The server side network interface should have access to a single VLAN.

Blade Servers (2:2)

- Blade servers, of which Cisco UCS is but one example, do not have sufficient independent network cards to avoid the networking becoming a single point of failure
- It is good when the public interface has a "keep alive" enabled but this is a fatal flaw for the cluster interconnect as fail-over will be delayed
- When different types of packets, public, storage, and interconnect are mixed low-level diagnostics are difficult ... if not impossible
- When different types of packets, public, storage, and interconnect are mixed the latency of one is the latency of all
- Traffic from any one blade can impact all blades



Troubleshooting gc block lost and Poor Network Performance in a RAC Environment (Doc ID 563566.1)

6. Interconnect LAN non-dedicated

Description: **Shared public IP traffic and/or shared NAS IP traffic, configured on the interconnect LAN will result in degraded application performance, network congestion and, in extreme cases, global cache block loss.**

Action: **The interconnect/clusterware traffic should be on a dedicated LAN defined by a non-routed subnet.** Interconnect traffic should be isolated to the adjacent switch(es), e.g. interconnect traffic should not extend beyond the access layer switch(es) to which the links are attached. **The interconnect traffic should not be shared with public or NAS traffic.** If Virtual LANs (VLANs) are used, the interconnect should be on a single, dedicated VLAN mapped to a dedicated, non-routed subnet, which is isolated from public or NAS traffic.

I/O (1:3)

- Not all HBA cards are the same
- NIC cards vary widely in capabilities and performance
 - TCP/IP Off-loading
 - Kernel Optimization of the TCP/IP stack

```
--enable TCP kernel auto-tuning
/proc/sys/net/ipv4/tcp_moderate_rcvbuf (1=on)

-- tune TCP max memory: tune to 2xBDP (Bandwidth x Delay Product)
-- For example, with 40 Mbits/sec bandwidth, 25 msec delay,
-- BDP = (40 x 1000 / 8 Kbytes/sec) x (0.025 sec) ~ 128 Kbytes
/proc/sys/net/ipv4/tcp_rmem and tcp_wmem 4096 87380 174760

-- tune the socket buffer sizes by setting to 2xBDP
/proc/sys/net/core/rmem_max and wmem_max

-- ensure that TCP Performance features are enabled
/proc/sys/net/ipv4/tcp_sack
/proc/sys/net/ipv4/tcp_window_scaling
/proc/sys/net/ipv4/tcp_timestamps

-- additionally be sure NIC cards have TCP off-loading capability
```

I/O (2:3)

- Optimize SQL*Net

```
--sqlnet.ora
NAMES.DIRECTORY_PATH= (TNSNAMES, EZCONNECT)
DEFAULT_SDU_SIZE=32767

-- listener.ora
DGLOGSHIPB =
  (DESCRIPTION =
    (SDU = 32767)
    (SEND_BUF_SIZE=9375000)
    (RECV_BUF_SIZE=9375000)
    (ADDRESS_LIST =
      (ADDRESS = (PROTOCOL = TCP) (HOST = 10.0.7.2) (PORT = 1526))
    )
    (CONNECT_DATA =
      (SERVICE_NAME = prodb)
    )
  )
)
```

I/O (3:3)

- Optimize for RAC

- Read the Oracle installation documents with very careful attention to the advice given for kernel parameters
- If on Linux and you don't know what rmem and wmem are ... read the docs
- If on Solaris and you don't know what rsize and wsize are ... read the docs

NUMA Memory Allocation

- Non-Uniform Memory Access
 - A memory design used in multiprocessing, where the memory access time depends on the memory location relative to the processor
 - A processor can access its own local memory faster than non-local memory
 - The benefits of NUMA are limited to particular workloads, notably on servers where the data are often associated strongly with certain tasks or users




Diagram Source: Wikipedia

Detect NUMA Use

NUMA Not Configured

```
[oracle@alpha1 ~]$ numactl --hardware
available: 1 nodes (0)
node 0 size: 4095 MB
node 9 free: 648MB
node distances:
node  0
  0:  10
```

```
[oracle@alpha1 ~]$ numactl --show
policy: default
preferred node: current
physcpubind: 0
nodebind: 0
membind: 0
```

NUMA Configured

```
[dmorgan@lخورap1n5 ~]$ numactl --hardware
available: 2 nodes (0-1)
node 0 size: 48457 MB
node 0 free: 269 MB
node 1 size: 48480 MB
node 1 free: 47 MB
node distances:
node  0  1
  0:  10  20
  1:  20  10
```

```
[dmorgan@lخورap1n5 ~]$ numactl --show
policy: default
preferred node: current
physcpubind: 0 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23
cpubind: 0 1
nodebind: 0 1
membind: 0 1
```

Is Your Database NUMA Aware?

```
SQL> SELECT a.ksppinm PNAME, c.ksppstvl PVAL, a.ksppdesc PDESC
2 FROM x$ksppi a, x$ksppcv b, x$ksppsv c
3 WHERE a.indx = b.indx
4 AND a.indx = c.indx
5 AND LOWER(a.ksppinm) LIKE '%numa%'
6* ORDER BY 1;
```

PNAME	PVAL	PDESC
-----	-----	-----
_NUMA_instance_mapping	Not specified	Set of nodes that this instance should run on
_NUMA_pool_size	Not specified	aggregate size in bytes of NUMA pool
_db_block_numa	1	Number of NUMA nodes
_enable_NUMA_interleave	TRUE	Enable NUMA interleave mode
_enable_NUMA_optimization	FALSE	Enable NUMA specific optimizations
_enable_NUMA_support	FALSE	Enable NUMA support and optimizations
_numa_buffer_cache_stats	0	Configure NUMA buffer cache stats
_numa_shift_enabled	TRUE	Enable NUMA shift
_numa_shift_value	0	user defined value for numa nodes shift
_numa_trace_level	0	numa trace event
_px_numa_stealing_enabled	TRUE	enable/disable PQ granule stealing across NUMA nodes
_px_numa_support_enabled	FALSE	enable/disable PQ NUMA support
_rm_numa_sched_enable	FALSE	Is Resource Manager (RM) related NUMA scheduled policy enabled
_rm_numa_simulation_cpus	0	number of cpus for each pg for numa simulation in resource mgr
_rm_numa_simulation_pgs	0	number of PGs for numa simulation in resource manager

Enable Database NUMA Support

```
conn / as sysdba
```

```
ALTER SYSTEM SET "_enable_NUMA_support" = TRUE  
COMMENT= 'NUMA Support Enabled 15-Mar-2015'  
CONTAINER=ALL  
SCOPE=SPFILE  
SID='*';
```

HugePages

- Also known as "Large Memory Pages" or just "Large Pages"
- Each page table entry represents a “virtual to physical” translation of a process’s memory
- Can be as large as 64 KB in size per entry
- Can be huge for large memory systems
 - See PageTables in /proc/meminfo
 - As large as 1.5 GB
- The entire SGA must fit inside the HugePages. If it does not fit none of it will use the HugePage memory and you will essentially have walled your database off from using a large portion of the server's memory

Swapiness

- Swapping (aka Paging)
- In a sense the operating system's version of the Oracle Temp tablespace

Value	Strategy
vm.swapiness=0	The kernel will swap only to avoid an out of memory condition
vm.swapiness=60	The default value
vm.swapiness=100	The kernel will swap aggressively

Virtual Machines

- Leave sufficient cpu resources for the bare-metal operating system to perform I/O and manage network traffic
- Disable interrupt coalescing
- Disable chipset power management
- Read the docs
http://www.vmware.com/pdf/Perf_Best_Practices_vSphere5.0.pdf
- VMs on NUMA machines should be configured to enhance memory allocation
 - This example is from vSphere where 0 and 1 are the processor sockets

```
numa.nodeAffinity=0,1
```

Storage Hardware

- Storage
 - Spinning Disk
 - Solid State Devices
 - Controllers
 - SAN Switches

Device	Type	IOPS	Interface	Notes
7,200 rpm SATA drives	HDD	~75-100 IOPS ^[2]	SATA 3 Gbit/s	
10,000 rpm SATA drives	HDD	~125-150 IOPS ^[2]	SATA 3 Gbit/s	
10,000 rpm SAS drives	HDD	~140 IOPS ^[2]	SAS	
15,000 rpm SAS drives	HDD	~175-210 IOPS ^[2]	SAS	

Kaminario K2	Flash/DRAM /Hybrid SSD	Up to 1,200,000 IOPS SPC-1 IOPS with the K2-D (DRAM) ^{[41][42]}	FC	
NetApp FAS6240 cluster	Flash/Disk	1,261,145 SPECsfs2008 nfsv3 IOPS using 1,440 15K disks, across 60 shelves, with virtual storage tiering. ^[43]	NFS, CIFS, FC, FCoE, iSCSI	SPECsfs2008 is the latest version of the Standard Performance Evaluation Corporation benchmark suite measuring file server throughput and response time, providing a standardized method for comparing performance across different vendor platforms. http://www.spec.org/sfs2008
Fusion-io ioDrive2	SSD	Up to 9,608,000 IOPS ^[44]	PCIe	Only via demonstration so far.

Storage Heat Map



Daniel A. Morgan | damorgan12c@gmail.com | www.morganslibrary.org



Object Optimizations

- Oracle's default tablespace settings waste disk and create unnecessary I/O
 - Often a smallfile tablespace is a bad choice
- Default table creations are almost always inefficient
 - Often heap tables are a bad choice
- Not every index should be a default B*Tree
 - And poor choices lead to poor performance
- Oracle sequence object defaults are almost always inefficient
 - A default cache size of 20 is 99.9% of the time a bad choice
- The vast majority of PL/SQL I see written would have been valid in version 7.3.4
 - I've almost never seen constants declared properly
- Oracle optimizes data dictionary performance by clustering tables ... do you?

I'm Not Afraid To Show You Mine



Complete List of SQL Text

Daniel A. Morgan | damorgan12c@gmail.com | www.morganslibrary.org

[illegible]

Page Three

[illegible]

[illegible]

Page Five

```
when trunc(datetime_ins, 'mi') > trunc(sysdate)+7/24 then MSC end) summarised_late_count, count(distinct case when trunc(datetime_ins, 'mi') < trunc(sysdate)+7/24 then MSC end) summarised_ontime_count, sum(entries)
num_of_sunrows from NORTEL_PSCORE.VLR6_DY where datetime = trunc(sysdate)-1 )sumt union all SELECT 'NORTEL_PSCORE.GSCGMM' AS TABLENAME, sunday, CASE WHEN percent(summarised_ontime_count, (ontime_count-
late_count), 2) > 100 THEN 100 ELSE percent(summarised_ontime_count, (ontime_count-late_count), 2) END percent_of_cutoff, case when 100-percent(summarised_ontime_count, (ontime_count-late_count), 2) < 0 then 0 else
100-percent(summarised_ontime_count, (ontime_count-late_count), 2) end percent_of_cutoff_not_summed, percent(summarised_ontime_count, (ontime_count-late_count), 2)percentage_of_total_by5am,
percent(summarised_ontime_count+summarised_late_count, (ontime_count+late_count), 2) current_percentage, (ontime_count+late_count) current_raw_elements, summarised_ontime_count+summarised_late_count
current_summary_elements, summarised_ontime_count-summarised_late_count SUM_ELEMENTS_AT5AM, late_count late_raw_elements, (ontime_count-late_count) available_at_cutoff, percent(num_of_sunrows, num_of_rows, 2)
accuracy from ( select count(distinct case when trunc(datetime_ins, 'mi') > trunc(sysdate)+3/24 then SGSN end) late_count, count(distinct case when trunc(datetime_ins, 'mi') < trunc(sysdate)+3/24 then SGSN end) ontime_count, count
(*) num_of_rows from NORTEL_PSCORE.GSCGMM where datetime between trunc(sysdate)-1 and trunc(sysdate)-1/24/60 )rawt, ( select max(datetime)sunday, count(distinct case when trunc(datetime_ins, 'mi') > trunc(sysdate)+7/24
then SGSN end) summarised_late_count, count(distinct case when trunc(datetime_ins, 'mi') < trunc(sysdate)+7/24 then SGSN end) summarised_ontime_count, sum(entries) num_of_sunrows from NORTEL_PSCORE.GSCGMM_DY where
datetime = trunc(sysdate)-1 )sumt union all SELECT 'NORTEL_PSCORE.GSCSM_ACT' AS TABLENAME, sunday, CASE WHEN percent(summarised_ontime_count, (ontime_count-late_count), 2) > 100 THEN 100 ELSE
percent(summarised_ontime_count, (ontime_count-late_count), 2) END percent_of_cutoff, case when 100-percent(summarised_ontime_count, (ontime_count-late_count), 2) < 0 then 0 else 100-percent(summarised_ontime_count,
(ontime_count-late_count), 2) end percent_of_cutoff_not_summed, percent(summarised_ontime_count, (ontime_count+late_count), 2)percentage_of_total_by5am, percent(summarised_ontime_count+summarised_late_count,
ontime_count+late_count, 2) current_percentage, (ontime_count+late_count) current_raw_elements, summarised_ontime_count+summarised_late_count current_summary_elements, summarised_ontime_count-summarised_late_count
SUM_ELEMENTS_AT5AM, late_count late_raw_elements, (ontime_count-late_count) available_at_cutoff, percent(num_of_sunrows, num_of_rows, 2) accuracy from ( select count(distinct case when trunc(datetime_ins, 'mi') >
trunc(sysdate)+3/24 then SGSN end) late_count, count(distinct case when trunc(datetime_ins, 'mi') < trunc(sysdate)+3/24 then SGSN end) ontime_count, count (*) num_of_rows from NORTEL_PSCORE.GSCSM_ACT where datetime
between trunc(sysdate)-1 and trunc(sysdate)-1/24/60 )rawt, ( select max(datetime)sunday, count(distinct case when trunc(datetime_ins, 'mi') > trunc(sysdate)+7/24 then SGSN end) summarised_late_count, count(distinct case when
trunc(datetime_ins, 'mi') < trunc(sysdate)+7/24 then SGSN end) summarised_ontime_count, sum(entries) num_of_sunrows from NORTEL_PSCORE.GSCSM_ACT_DY where datetime = trunc(sysdate)-1 )sumt union all SELECT
'NORTEL_PSCORE.GSCSM' AS TABLENAME, sunday, CASE WHEN percent(summarised_ontime_count, (ontime_count-late_count), 2) > 100 THEN 100 ELSE percent(summarised_ontime_count, (ontime_count-late_count), 2) END
percent_of_cutoff, case when 100-percent(summarised_ontime_count, (ontime_count-late_count), 2) < 0 then 0 else 100-percent(summarised_ontime_count, (ontime_count-late_count), 2) end percent_of_cutoff_not_summed,
percent(summarised_ontime_count, (ontime_count+late_count), 2)percentage_of_total_by5am, percent(summarised_ontime_count+summarised_late_count, (ontime_count+late_count), 2) current_percentage, (ontime_count+late_count)
current_raw_elements, summarised_ontime_count+summarised_late_count current_summary_elements, summarised_ontime_count-summarised_late_count SUM_ELEMENTS_AT5AM, late_count late_raw_elements, (ontime_count-
late_count) available_at_cutoff, percent(num_of_sunrows, num_of_rows, 2) accuracy from ( select count(distinct case when trunc(datetime_ins, 'mi') > trunc(sysdate)+3/24 then SGSN end) late_count, count(distinct case when
trunc(datetime_ins, 'mi') < trunc(sysdate)+3/24 then SGSN end) ontime_count, count (*) num_of_rows from NORTEL_PSCORE.GSCSM where datetime between trunc(sysdate)-1 and trunc(sysdate)-1/24/60 )rawt, ( select
max(datetime)sunday, count(distinct case when trunc(datetime_ins, 'mi') > trunc(sysdate)+7/24 then SGSN end) summarised_late_count, count(distinct case when trunc(datetime_ins, 'mi') < trunc(sysdate)+7/24 then SGSN end)
summarised_ontime_count, sum(entries) num_of_sunrows from NORTEL_PSCORE.GSCSM_DY where datetime = trunc(sysdate)-1 )sumt union all SELECT 'NORTEL_PSCORE.GSDSTATS' AS TABLENAME, sunday, CASE WHEN
percent(summarised_ontime_count, (ontime_count-late_count), 2) > 100 THEN 100 ELSE percent(summarised_ontime_count, (ontime_count-late_count), 2) END percent_of_cutoff, case when 100-percent(summarised_ontime_count,
(ontime_count-late_count), 2) < 0 then 0 else 100-percent(summarised_ontime_count, (ontime_count-late_count), 2) end percent_of_cutoff_not_summed, percent(summarised_ontime_count, (ontime_count+late_count),
2)percentage_of_total_by5am, percent(summarised_ontime_count+summarised_late_count, (ontime_count+late_count), 2) current_percentage, (ontime_count+late_count) current_raw_elements,
summarised_ontime_count+summarised_late_count current_summary_elements, summarised_ontime_count-summarised_late_count SUM_ELEMENTS_AT5AM, late_count late_raw_elements, (ontime_count-late_count) available_at_cutoff,
percent(num_of_sunrows, num_of_rows, 2) accuracy from ( select count(distinct case when trunc(datetime_ins, 'mi') > trunc(sysdate)+3/24 then SGSN end) late_count, count(distinct case when trunc(datetime_ins, 'mi') <
trunc(sysdate)+3/24 then SGSN end) ontime_count, count (*) num_of_rows from NORTEL_PSCORE.GSDSTATS where datetime between trunc(sysdate)-1 and trunc(sysdate)-1/24/60 )rawt, ( select max(datetime)sunday, count(distinct
case when trunc(datetime_ins, 'mi') > trunc(sysdate)+7/24 then SGSN end) summarised_late_count, count(distinct case when trunc(datetime_ins, 'mi') < trunc(sysdate)+7/24 then SGSN end) summarised_ontime_count, sum(entries)
num_of_sunrows from NORTEL_PSCORE.GSDSTATS_DY where datetime = trunc(sysdate)-1 )sumt
```

Optimizer Plans (1:4)

```
SELECT DISTINCT E1_2.OBJECT_ID
FROM PMCM.ELEMENT_DETAIL E1_1, PMCM.ELEMENT_DETAIL E1_2, PMCM.MARK_NETW_HIERARCHY H1,
PMCM.ELEMENT_DETAIL E2_1, PMCM.ELEMENT_DETAIL E2_2, PMCM.MARK_NETW_HIERARCHY H2
WHERE E1_1.OBJECT_ID = H1.PARENT_ID
AND E1_2.OBJECT_ID = H1.OBJECT_ID
AND E2_1.OBJECT_ID = H2.PARENT_ID
AND E2_2.OBJECT_ID = H2.OBJECT_ID
AND E1_1.CURRENT_IND = 'Y' AND E2_1.CURRENT_IND = 'Y'
AND E2_1.CURRENT_IND = 'Y' AND E2_2.CURRENT_IND = 'Y'
AND H1.CURRENT_IND = 'Y' AND H2.CURRENT_IND = 'Y'
AND H1.HIERARCHY_TYPE = 'NETWORK' AND H2.HIERARCHY_TYPE = 'NETWORK'
AND H1.PARENT_TYPE IN ('BSC','RNC') AND H2.PARENT_TYPE IN ('BSC','RNC')
AND E2_2.ELEMENT_TYPE = 'CELL' AND E1_2.ELEMENT_TYPE = 'CELL'
AND H1.PARENT_TYPE IN ('BSC','RNC')
AND E1_1.ELEMENT_NAME = E2_1.ELEMENT_NAME
AND E1_1.ELEMENT_ID = E2_1.ELEMENT_ID
AND E1_2.ELEMENT_NAME = E2_2.ELEMENT_NAME
AND E1_2.ELEMENT_ID = E2_2.ELEMENT_ID
AND E1_2.USEID LIKE '*%' AND E2_2.USEID NOT LIKE '*%';
```

Id	Operation	Name	Rows	Bytes	TempSpc	Cost (%CPU)	Time	Pstart	Pstop
0	SELECT STATEMENT		1	78		74M (40)	50:54:42		
1	TEMP TABLE TRANSFORMATION								
2	LOAD AS SELECT								
3	PARTITION RANGE ALL		22M	1111M		38153 (11)	00:01:34	1	29
* 4	TABLE ACCESS FULL	ELEMENT_DETAIL	22M	1111M		38153 (11)	00:01:34		
5	LOAD AS SELECT								
6	PARTITION HASH ALL		337K	9231K		3514 (15)	00:00:09	1	16
* 7	TABLE ACCESS FULL	MARK_NETW_HIERARCHY	337K	9231K		3514 (15)	00:00:09		
8	SORT AGGREGATE		1	78					
* 9	HASH JOIN		927G	65T	534M	74M (40)	50:53:00		
10	VIEW		22M	277M		16808 (12)	00:00:42		
11	TABLE ACCESS FULL	SYS_TEMP_OFDA7485F_6A66C42E	22M	1111M		16808 (12)	00		
* 12	HASH JOIN		21G	1272G	534M	1616K (43)	01:06:04		
13	VIEW		22M	277M		16808 (12)	00:00:42		
14	TABLE ACCESS FULL	SYS_TEMP_OFDA7485F_6A66C42E	22M	1111M		16808 (12)	0		
* 15	HASH JOIN		476M	23G	524M	97327 (22)	00:03:59		
* 16	HASH JOIN		10M	401M	8704K	34520 (10)	00:01:25		
* 17	HASH JOIN		234K	5948K	8256K	783 (10)	00:00:02		
18	VIEW		337K	4286K		142 (14)	00:00:01		
19	TABLE ACCESS FULL	SYS_TEMP_OFDA74860_6A66C42E	337K	3956K		142 (14)	00:00:01		
20	VIEW		337K	4286K		142 (14)	00:00:01		
21	TABLE ACCESS FULL	SYS_TEMP_OFDA74860_6A66C42E	337K	3956K		142 (14)	00:00:01		
22	VIEW		22M	277M		16808 (12)	00:00:42		
23	TABLE ACCESS FULL	SYS_TEMP_OFDA7485F_6A66C42E	22M	1111M		16808 (12)	00:00:42		
24	VIEW		22M	277M		16808 (12)	00:00:42		
25	TABLE ACCESS FULL	SYS_TEMP_OFDA7485F_6A66C42E	22M	1111M		16808 (12)	0		

Optimizer Plans (2:4)

Id	Operation	Name	Rows	Bytes	TempSpc	Cost (%CPU)	Time	Pstart	Pstop
0	SELECT STATEMENT		1	78		14T (100)	999:59:59		
1	TEMP TABLE TRANSFORMATION								
2	LOAD AS SELECT								
3	PARTITION RANGE ALL		22M	1111M		38153 (11)	00:01:34	1	29
* 4	TABLE ACCESS FULL	ELEMENT_DETAIL	22M	1111M		38153 (11)	00:01:34		
5	LOAD AS SELECT								
6	PARTITION HASH ALL		337K	9231K		3514 (15)	00:00:09	1	16
* 7	TABLE ACCESS FULL	MARK_NETW_HIERARCHY	337K	9231K		3514 (15)	00:00:09		
8	SORT AGGREGATE		1	78					
9	MERGE JOIN		471P	15E		14T (100)	999:59:59		
10	MERGE JOIN		10P	616P		694G (81)	999:59:59		
11	MERGE JOIN		231T	10P		377G (64)	999:59:59		
12	SORT JOIN		334T	11P	28P	377G (64)	999:59:59		
13	MERGE JOIN CARTESIAN		334T	11P		140G (14)	999:59:59		
* 14	HASH JOIN		989M	23G	534M	96010 (38)	00:03:56		
15	VIEW		22M	277M		16808 (12)	00:00:42		
16	TABLE ACCESS FULL	SYS_TEMP_OFDA7485B_6A66C42E	22M	1111M		16808 (12)	00:00:42		
17	VIEW		22M	277M		16808 (12)	00:00:42		
18	TABLE ACCESS FULL	SYS_TEMP_OFDA7485B_6A66C42E	22M	1111M		16808 (12)	00:00:42		
19	BUFFER SORT		337K	4286K		140G (14)	999:59:59		
20	VIEW		337K	4286K		142 (14)	00:00:01		
21	TABLE ACCESS FULL	SYS_TEMP_OFDA7485C_6A66C42E	337K	3956K		142 (14)	00:00:01		
* 22	SORT JOIN		337K	4286K	12M	844 (14)	00:00:03		
23	VIEW		337K	4286K		142 (14)	00:00:01		
24	TABLE ACCESS FULL	SYS_TEMP_OFDA7485C_6A66C42E	337K	3956K		142 (14)	00:00:01		
* 25	SORT JOIN		22M	277M	855M	65084 (16)	00:02:40		
26	VIEW		22M	277M		16808 (12)	00:00:42		
27	TABLE ACCESS FULL	SYS_TEMP_OFDA7485B_6A66C42E	22M	1111M		16808 (12)	0		
* 28	SORT JOIN		22M	277M	855M	65084 (16)	00:02:40		
29	VIEW		22M	277M		16808 (12)	00:00:42		
30	TABLE ACCESS FULL	SYS_TEMP_OFDA7485B_6A66C42E	22M	1111M		16808 (12)	0		

Optimizer Plans (3:4)

```
WITH ed AS (SELECT object_id, element_id, element_name, element_type, useid
            FROM pmcm.element_detail
            WHERE element_type = 'CELL'
            AND current_ind = 'Y'),
     mn AS (SELECT parent_id, object_id
            FROM pmcm.mark_netw_hierarchy
            WHERE current_ind = 'Y'
            AND hierarchy_type = 'NETWORK'
            AND parent_type IN ('BSC', 'RNC'))
SELECT COUNT(*)
FROM ed e1_1, ed e1_2, ed e2_1, ed e2_2, mn h1, mn h2
WHERE e1_1.object_id = h1.parent_id AND e1_2.object_id = h1.object_id
AND e2_1.object_id = h2.parent_id AND e2_2.object_id = h2.object_id
AND e1_1.element_name = e2_1.element_name
AND e1_1.element_id = e2_1.element_id
AND e1_2.element_name = e2_2.element_name
AND e1_2.element_id = e2_2.element_id
AND e1_2.useid LIKE '%%'
AND e2_2.useid NOT LIKE '%%';
```

Id	Operation	Name	Rows	Bytes	TempSpc	Cost (%CPU)	Time
0	SELECT STATEMENT		1	214		100K (6)	00:04:08
1	HASH UNIQUE		1	214		100K (6)	00:04:08
* 2	HASH JOIN		1	214	12M	100K (6)	00:04:08
3	PARTITION HASH ALL		337K	9231K		3514 (15)	00:00:09
* 4	TABLE ACCESS FULL	MARK_NETW_HIERARCHY	337K	9231K		3514 (15)	00:00:00
* 5	HASH JOIN		207K	36M	22M	95860 (6)	00:03:56
6	PARTITION RANGE ALL		586K	15M		16233 (2)	00:00:40
7	TABLE ACCESS BY LOCAL INDEX ROWID	ELEMENT_DETAIL	586K	15M		16233	???:??:??
* 8	INDEX SKIP SCAN	ED_ET_TECH_CI	586K			12791 (1)	00:00:3?
* 9	HASH JOIN		207K	31M	22M	77982 (7)	00:03:12
10	PARTITION RANGE ALL		586K	15M		16233 (2)	00:00:40
11	TABLE ACCESS BY LOCAL INDEX ROWID	ELEMENT_DETAIL	586K	15M		16233	???:??:??
* 12	INDEX SKIP SCAN	ED_ET_TECH_CI	586K			12791 (1)	00:00:??
* 13	HASH JOIN		179K	22M	12M	60372 (8)	00:02:29
14	PARTITION HASH ALL		337K	9231K		3514 (15)	00:00:09
* 15	TABLE ACCESS FULL	MARK_NETW_HIERARCHY	337K	9231K		3514 (15)	00:00:??
* 16	HASH JOIN		184K	17M	10M	55886 (8)	00:02:18
17	PARTITION RANGE ALL		184K	9008K		37137 (8)	00:01:32
* 18	TABLE ACCESS FULL	ELEMENT_DETAIL	184K	9008K		37137 (8)	00:01:32
19	PARTITION RANGE ALL		576K	28M		17383 (8)	00:00:43
* 20	TABLE ACCESS BY LOCAL INDEX ROWID	ELEMENT_DETAIL	576K	28M		17383 (8)	???:??:??
* 21	INDEX SKIP SCAN	ED_ET_TECH_CI	583K			13939 (9)	00:00:35

Optimizer Plans (4:4)

Id	Operation	Name	Rows	Bytes	TempSpc	Cost (%CPU)	Time
0	SELECT STATEMENT					264T (100)	
* 1	VIEW		156P	15E		264T (79) 999:59:59	
* 2	WINDOW SORT PUSHED RANK		156P	15E	15E	264T (79) 999:59:59	
3	MERGE JOIN CARTESIAN		156P	15E		68T (16) 999:59:59	
4	MERGE JOIN CARTESIAN		220G	205T		96M (16) 26:57:48	
5	MERGE JOIN CARTESIAN		310K	302M		232 (11) 00:00:01	
6	MERGE JOIN CARTESIAN		779	777K		22 (0) 00:00:01	
7	NESTED LOOPS						
8	NESTED LOOPS		2	2044		20 (0) 00:00:01	
9	NESTED LOOPS OUTER		2	1990		18 (0) 00:00:01	
10	NESTED LOOPS		2	1868		17 (0) 00:00:01	
11	NESTED LOOPS		2	1712		15 (0) 00:00:01	
12	NESTED LOOPS		2	1564		13 (0) 00:00:01	
13	MERGE JOIN CARTESIAN		2	1442		11 (0) 00:00:01	
14	NESTED LOOPS OUTER		1	625		8 (0) 00:00:01	
15	NESTED LOOPS OUTER		1	613		7 (0) 00:00:01	
16	NESTED LOOPS		1	580		6 (0) 00:00:01	
17	NESTED LOOPS OUTER		1	539		5 (0) 00:00:01	
18	NESTED LOOPS OUTER		1	340		5 (0) 00:00:01	
19	TABLE ACCESS BY INDEX ROWID	PA_STUDENT	1	316		3 (0) 00:00:01	
* 20	INDEX UNIQUE SCAN	PK_STUDENT	1			2 (0) 00:00:01	
21	TABLE ACCESS BY INDEX ROWID	PA_STUD_USER	1	24		2 (0) 00:00:01	
* 22	INDEX UNIQUE SCAN	PK_STUD_USER	1			1 (0) 00:00:01	
23	TABLE ACCESS BY INDEX ROWID	PA_ORG	1	199		0 (0)	
* 24	INDEX UNIQUE SCAN	PK_ORG	1			0 (0)	
25	TABLE ACCESS BY INDEX ROWID	PA_DOMAIN	13	533		1 (0) 00:00:01	
* 26	INDEX UNIQUE SCAN	PK_DOMAIN	1			0 (0)	
27	TABLE ACCESS BY INDEX ROWID	PA_USRRF_STUD	100	3300		1 (0) 00:00:01	
* 28	INDEX UNIQUE SCAN	PK_USRRF_STUD	1			0 (0)	
29	VIEW PUSHED PREDICATE	PV_STUD_USER	1	12		1 (0) 00:00:01	
* 30	FILTER						
31	NESTED LOOPS OUTER		1	22		264 (11) 00:00:01	
* 32	INDEX UNIQUE SCAN	PK_STUDENT	1	10		2 (0) 00:00:01	
* 33	MAT_VIEW ACCESS FULL	PV_AP_STUD_USER	1	12		262 (11) 00:00:01	
34	BUFFER SORT		2	192		10 (0) 00:00:01	
35	TABLE ACCESS BY INDEX ROWID	PA_CPNT_COMPLIANCE_DATA	2	192		3 (0) 00:00:01	
* 36	INDEX RANGE SCAN	IX_CPNT_CD__EVTHST	2			1 (0) 00:00:01	
37	TABLE ACCESS BY INDEX ROWID	PA_CPNT_TYPE	1	61		1 (0) 00:00:01	
* 38	INDEX UNIQUE SCAN	PK_CPNT_TYPE	1			0 (0)	
39	TABLE ACCESS BY INDEX ROWID	PA_RQMT_TYPE	1	74		1 (0) 00:00:01	
* 40	INDEX UNIQUE SCAN	PK_RQMT_TYPE	1			0 (0)	
41	TABLE ACCESS BY INDEX ROWID	PA_CMPL_STAT	1	78		1 (0) 00:00:01	
* 42	INDEX UNIQUE SCAN	PK_CMPL_STAT	1			0 (0)	
43	TABLE ACCESS BY INDEX ROWID	PA_QUAL	1	61		1 (0) 00:00:01	
* 44	INDEX UNIQUE SCAN	PK_QUAL	1			0 (0)	
* 45	INDEX UNIQUE SCAN	PK_CPNT	1			0 (0)	
46	TABLE ACCESS BY INDEX ROWID	PA_CPNT	1	27		1 (0) 00:00:01	
47	BUFFER SORT		399			21 (0) 00:00:01	
48	INDEX FAST FULL SCAN	PK_USRRF_STUD	399			1 (0) 00:00:01	
49	BUFFER SORT		399			231 (11) 00:00:01	
50	INDEX FAST FULL SCAN	PK_USRRF_STUD	399			0 (0)	
51	BUFFER SORT		710K			96M (16) 26:57:48	
52	INDEX FAST FULL SCAN	IX_STUD_USER__STUDENT	710K			309 (16) 00:00:01	
53	BUFFER SORT		710K			264T (79) 999:59:59	
54	INDEX FAST FULL SCAN	IX_STUD_USER__STUDENT	710K			309 (16) 00:00:01	

Poorly Written Applications

SQL ordered by Executions

- Total Executions: 29,717,627
- Captured SQL account for 77.4% of Total

Executions	Rows Processed	Rows per Exec	CPU per Exec (s)	Elap per Exec (s)	SQL Id	SQL Module	SQL Text
10,128,178	2,506,529	0.25	0.00	0.00	932srzq1krc33	ASN_07B_DIP(004110016)	SELECT NE_TIMEZONE FROM CMPME...
7,576,759	7,579,197	1.00	0.00	0.00	1h698sb62un99	asci_56_RANAPProtocolStats(01611000E)	SELECT DISTINCT NE_TIMEZONE FR...
3,914,621	3,848,268	0.98	0.00	0.00	5tbzddgguu8cc	asci_56_RANAPProtocolStats(01611000E)	SELECT SYS_VERSION FROM CMPM.T...
311,845	311,804	1.00	0.00	0.00	7qztz329wq0		select c.name, u.name from co...
301,428	301,325	1.00	0.00	0.00	36s446f9cnwhw		SELECT C.NAME FROM COL\$ C VHER...
200,692	200,669	1.00	0.00	0.00	4vs91dcv7urfp6	OMS	insert into sys.aud\$(sessioni...
65,044	65,035	1.00	0.00	0.00	fz9xwpt2cvt0k		SELECT par_type, param_clob, ...
64,949	3,945,482	60.75	0.00	0.00	f5ra7dru5fk5n	XML_P7R_RNC_RCS(003110008)	SELECT NAME, PATH, READ, WR...
64,801	64,807	1.00	0.00	0.00	fhzi09a7fmrnb	XML_V7I_IN_LP_DC(00811000V)	SELECT DBTIMEZONE, LENGTH(DBT...
64,632	64,542	1.00	0.00	0.00	15inrrb6016nd	XML_V7I_IN_LP_DC(00811000V)	SELECT SESSIONTIMEZONE, LENGT...

```

SELECT /*+ RESULT_CACHE */ srvr_id
FROM (
  SELECT srvr_id, SUM(cnt) SUMCNT
  FROM (
    SELECT DISTINCT srvr_id, 1 AS CNT
    FROM servers
    UNION ALL
    SELECT DISTINCT srvr_id, 1
    FROM serv_inst)
  GROUP BY srvr_id)
WHERE sumcnt = 2;

```

Optimizer Settings

- Default Oracle install favors data warehouse not OLTP

NAME	TYPE	VALUE
optimizer_adaptive_features	boolean	TRUE
optimizer_adaptive_reporting_only	boolean	FALSE
optimizer_capture_sql_plan_baselines	boolean	FALSE
optimizer_dynamic_sampling	integer	2
optimizer_features_enable	string	12.1.0.2
optimizer_index_caching	integer	0
optimizer_index_cost_adj	integer	100
optimizer_mode	string	ALL_ROWS
optimizer_secure_view_merging	boolean	TRUE
optimizer_use_invisible_indexes	boolean	FALSE
optimizer_use_pending_statistics	boolean	FALSE
optimizer_use_sql_plan_baselines	boolean	TRUE

```
SQL> show parameter optimizer_mode
```

NAME	TYPE	VALUE
optimizer_mode	string	ALL_ROWS

← Best for Data Warehouse

```
SQL> ALTER SYSTEM SET OPTIMIZER_MODE='FIRST_ROWS_10';
```

System altered.

```
SQL> show parameter optimizer_mode
```

NAME	TYPE	VALUE
optimizer_mode	string	FIRST_ROWS_10

← Best for OLTP

Optimizer Statistics

- Gather System Stats
- Gather Fixed Object Stats
- Gather Dictionary Stats
- Gather Table Stats
- Gather Column Stats
- Gather Index Stats
- Gather Extended Stats
- Stat Generation
 - Copy Stats
 - Set Stats
 - Fixing Stats

```
Terminal
Window Edit Options
MAXTHR
MBRC
MREADTIM
SLAVETHR
SREADTIM
9 rows selected.
SQL> /
PNAME-----PVAL1
CPUSPEED
CPUSPEEDNW        680.062427
IOSEEKTIM          10
IOTFRSPEED        4096
MAXTHR
MBRC
MREADTIM
SLAVETHR
SREADTIM
9 rows selected.
SQL> exec dbms_stats.gather_system_stats('STOP');
PL/SQL procedure successfully completed.
SQL> select pname, pval1
2   from aux_stats$
3  where sname = 'SYSSTATS_MAIN';
PNAME-----PVAL1
CPUSPEED
CPUSPEEDNW        680.062427
IOSEEKTIM          10
IOTFRSPEED        4096
MAXTHR
MBRC
MREADTIM          .107
SLAVETHR
SREADTIM          .029
9 rows selected.
SQL> █
```

```
SQL> select type, count(*)
2   from v$fixed_table
3  group by type
4  order by 1;
```

TYPE	COUNT(*)
TABLE	1144
VIEW	1261

```
SQL> select name
2   from v$fixed_table
3  where rownum < 11;
```

NAME
X\$KQFTA
X\$KQFVI
X\$KQFVT
X\$KQFDT
X\$KQFCO
X\$KQFOPT
X\$KYWMPCTAB
X\$KYWMWRCTAB
X\$KYWMCLTAB
X\$KYWMNF

Gathering Optimizer Statistics

```
exec dbms_stats.set_table_prefs(USER, 'SERVERS', 'ESTIMATE_PERCENT', '90');  
  
exec dbms_stats.set_table_prefs(USER, 'SERVERS', 'DEGREE', '8');
```

```
exec dbms_stats.gather_table_stats(USER, 'SERVERS',  
  'P2010103106',  
  estimate_percent => dbms_stats.auto_sample_size,  
  block_sample=>TRUE,  
  method_opt=>'FOR ALL INDEXED COLUMNS',  
  degree=>2,  
  cascade=>TRUE  
  force=>TRUE);
```

```
SELECT dbms_stats.create_extended_stats(USER, 'SERV_INST', '(srvr_id, si_status)')  
FROM dual;
```

Manufacturing Optimizer Statistics

```
exec dbms_stats.set_table_stats(USER, 'EMP', numrows=>1000000, numblks=>10000, avgrlen=>74);  
  
exec dbms_stats.set_index_stats(USER, 'ix_emp_deptno', numrows=>1000000, numblks=>1000,  
    numdist=>10000, clstfct=>1);  
  
exec dbms_stats.set_column_stats(USER, 'emp', 'deptno', distcnt=>10000);  
  
exec dbms_stats.set_table_stats(USER, 'dept', numrows=>100, numblks=>100);
```

Root Cause Analysis by Sophisticated Guessing

- Check data dictionary for collected stats
- Explain Plans
 - Very few people can read them ... I will prove it next
- AWR Reports
 - Data <> Information
 - If you want value from AWR ... create **AWR Difference** reports with **DBMS_WORKLOAD_REPOSITORY.AWR_DIFF_REPORT_HTML**
- ASH Reports
- SQL Tuning Advisor
- SQL Trace and TKPROF
- Baselines and Evolving Baselines
- DBMS_TRACE, DBMS_MONITOR, TRCSESS, TRACE ANALYZER, SQLTXPLAIN

Reading Explain Plans

- Very few people can read an explain plan
- Here are two plans from identical tables with identical stats
- Which one would you rely on?

Database 11gR2

Id	Operation	Name	Rows	Bytes	Cost (%CPU)
0	SELECT STATEMENT		141	4560	6 (84)
1	INTERSECTION				
2	SORT UNIQUE NOSORT		141	564	2 (50)
3	INDEX FULL SCAN	PK_SERVERS	141	564	1 (0)
4	SORT UNIQUE		999	3996	4 (25)
5	INDEX FAST FULL SCAN	IX_SERV_INST	999	3996	3 (0)

Id	Operation	Name	Rows	Bytes	Cost (%CPU)
0	SELECT STATEMENT		141	4560	20 (10)
1	INTERSECTION				
2	TABLE ACCESS FULL	SERVERS	141	564	10 (10)
4	SORT UNIQUE		999	3996	10 (10)
5	TABLE ACCESS FULL	SERV_INST	999	3996	9 (0)


Database 12gR1

The SQL Statement

```
SELECT srvr_id
FROM servers
INTERSECT
SELECT srvr_id
FROM serv_inst;
```

```
SQL> SELECT table_name, blocks
2 FROM user_tables
3* WHERE table_name IN ('SERVERS', 'SERV_INST');
```

TABLE_NAME	BLOCKS
SERVERS	28
SERV_INST	28



This Adds To The Confusion

```
SQL> SELECT blocks
2 FROM dba_tables
3 WHERE owner = 'UWCLASS'
4 AND table_name = 'SERVERS';
```

BLOCKS

28

```
SQL> SELECT blocks
2 FROM dba_segments
3 WHERE owner = 'UWCLASS'
4 AND segment_name = 'SERVERS';
```

BLOCKS

32

This Makes It Even Worse

```
SQL> DECLARE
  2  uf  NUMBER;
  3  ub  NUMBER;
  4  f1  NUMBER;
  5  f1b NUMBER;
  6  f2  NUMBER;
  7  f2b NUMBER;
  8  f3  NUMBER;
  9  f3b NUMBER;
 10  f4  NUMBER;
 11  f4b NUMBER;
 12  fbl NUMBER;
 13  fby NUMBER;
 14 BEGIN
 15  dbms_space.space_usage('UWCLASS','SERVERS', 'TABLE', uf, ub, f1, f1b, f2, f2b, f3, f3b, f4, f4b, fbl, fby);
 16
 17  dbms_output.put_line('unformatted blocks: ' || TO_CHAR(uf));
 18  dbms_output.put_line('unformatted bytes: ' || TO_CHAR(ub));
 19  dbms_output.put_line('blocks 0-25% free: ' || TO_CHAR(f1));
 20  dbms_output.put_line('bytes 0-25% free: ' || TO_CHAR(f1b));
 21  dbms_output.put_line('blocks 25-50% free: ' || TO_CHAR(f2));
 22  dbms_output.put_line('bytes 25-50% free: ' || TO_CHAR(f2b));
 23  dbms_output.put_line('blocks 50-75% free: ' || TO_CHAR(f3));
 24  dbms_output.put_line('bytes 50-75% free: ' || TO_CHAR(f3b));
 25  dbms_output.put_line('blocks 75-100% free: ' || TO_CHAR(f4));
 26  dbms_output.put_line('bytes 75-100% free: ' || TO_CHAR(f4b));
 27  dbms_output.put_line('full blocks: ' || TO_CHAR(fbl));
 28  dbms_output.put_line('full bytes: ' || TO_CHAR(fby));
 29 END;
 30 /
unformatted blocks: 16
unformatted bytes: 131072
blocks 0-25% free: 0
bytes 0-25% free: 0
blocks 25-50% free: 1
bytes 25-50% free: 8192
blocks 50-75% free: 0
bytes 50-75% free: 0
blocks 75-100% free: 11
bytes 75-100% free: 90112
full blocks: 0
full bytes: 0
```



only 12 blocks are formatted

Summary

- Do not guess
 - If your problem is not caused by slow hardware then faster hardware will just create a problem faster
 - Gather information from a date-time range when everything was good and compare with the date-time range when the problem was observed
 - If the problem is slow SQL ... is the SQL statement itself slow or is it the entire environment that should be examined?
 - If the problem is related to CPU ... do you need more/faster CPUs or a better design?
 - If the problem is related to I/O ... do you need a new SAN or better indexing?
 - If the problem is related to network bandwidth ... do you need new NIC cards and to stop network virtualization? Yes you probably do

Conclusion

- The No SQL approach to tuning is to stop guessing
 - And stop blaming everything on SQL statements
 - Until you can prove that the root cause is the SQL
 - Use the scientific method
 - Construct a hypothesis
 - Test the hypothesis by doing experiments
 - Validate your conclusion
 - Only rewrite SQL after you have established conclusively that the root cause is the way a statement has been written
-
- Most likely you will find yourself rewriting very little SQL

ERROR at line 1:
ORA-00028: your session has been killed



Thank you

Contact: damorgan@u.washington.edu
+1 206-669-2949
Skype: damorgan11g

For a copy of this presentation go to:
www.morganslibrary.org/presentations.html

Or contact me: damorgan@u.washington.edu
+1 206-669-2949
Skype: damorgan11g